

CEILING SYSTEMS  
CURVED

# 1010 series WINGS

A multi-dimensional ceiling profile. Can be used on walls & high levels. Light weight and fully demountable. An acoustic pad can added to improved acoustic performance. Offered in a wide range of sizes, colors & finishes.

## FEATURES

### MATERIAL

Aluminum Alloy as per EN AW 3000 or 5000 series.

### THICKNESS

Aluminum (mm)  
0.7 to 1.0

+ Custom thickness are available upon request

### SURFACE FINISH

Plain  
Perforated

### SIZE

WIDTH (mm): 600

LENGTH (mm): Up to 2000

+ Custom sizes are available upon request

### COATING

Polyester Coating: ( $5\mu$  (Back) +  $20\mu$  (Face))

Polyester Powder Coating: ( $70\mu$  -  $80\mu$ )


+ High Performance Coatings like PESDF, PVDF and POLYAMIDE are available upon request.

### INSULATION

**Acoustic Black Fleece** is non-flammable and meets the standard DIN 4102 / B1. Classification A1 according to EN 13501-1.

**Rockwool slabs** conforming to ASTM C612 and equivalent BS 3958-5 are provided for acoustic insulation.

### COLORS




### SPECIAL FINISHES



+ See [www.rammatal.com](http://www.rammatal.com) for additional colors & special finishes available

+ Special finishes can be provided in lamination, sublimation or coil coating process.

### PERFORATION PATTERNS



+ See [www.rammatal.com](http://www.rammatal.com) for all available pattern options

## DATA / PERFORMANCE



### ACOUSTICS

Tested as per BS EN ISO 354: 2003 for sound absorption, noise reduction and sound attenuation.

NRC achieved with Acoustic Black fleece – NRC 0.75

NRC achieved with Acoustic Black Fleece and Rockwool Insulation – NRC 1.00

Tested as per ASTM E1414-11a for Airborne Sound Attenuation as per ISO 10848-2.

CAC can achieved up to – 48 dB

Perforated & Sound Attenuation cover



### ANTI BACTERIAL COATING

Tested as per JIS Z 2801: 2000, which inhibits the growth of bacteria on the applied surface.



### LIGHT REFLECTANCE (LR)

Achieved by the metal ceiling is LR – 0.85-0.96 tested as per ASTM E 1477.



### FIRE PERFORMANCE


Surface Spread of flame Class 1 tested as per BS 476: Part 7: 1997

“Non-Combustible” Material tested as per BS 476: Part4: 1970

Flame Spread and Smoke Development Index tested as per ASTM E84 (Class 1 or A)

## RAM 1011 WINGS

### ISOMETRIC DETAIL




### COMPONENTS

- 1 Panel
- 2 Inverted L Bracket
- 3 Main Carrier
- 4 Threaded Rod •
- 5 Rigid Hanging System •
- 6 Anti-Vibration Clip •

• Optional

Custom sizes can be offered

### OPTIONAL HANGING SOLUTIONS



### PANEL JOINT DETAIL

